



Product: <u>9312</u> ☑

High Perform Instr, 1 Pr #12 Str TC, PVC Ins E2, OS, PVC Jkt, PLTC-ER

Request Sample

Product Description

High Performance Instrumentation, 1 Pair 12AWG (65x30) Tinned Copper, PVC Insulation E2 Color Code, Overall Beldfoil® Shield, PVC Outer Jacket, PLTC-ER

Technical Specifications

Suitable Applic	ole Applications: Instrumentation, Sensors, Valves, Positioners, 4-20mA, 0-10V					
onstructi	on Details					
onductor						
Element Nur	nber of Element	Size Stranding	Material			
Pair(s) 1		12 AWG 65x30	TC - Tinned Copper			
sulation						
Element	Material	Nom. Thickness	Nom. Insulation Diamet	er Color Code		
Pair(s) PV0	C - Polyvinyl Chloric	le 0.025 in (0.64 mn	0.143 in (3.63 mm)	Black, Red		
uter Shield Shield Type	Material	Coverage	Drainwire Type			
Гаре	Bi-Laminate (Alum	+Poly) 100%	4 AWG (19x26) TC			
uter Jacket						
Separator	Material	Nom. Thickr	ess Nom. Diameter F	Ripcord		
Cotton Serve	PVC - Polyvinyl Ch	nloride 0.042 in (1.1	mm) 0.373 in (9.47 mm)	'es		
Overall Cable	Diameter (Nominal)): 0.373 in (9.47 mm)			
loctrical (haracteristic					
ilectifical C	inar acteristic					
lectricals						
-1 1	n. Conductor DCR	Nom. Capacitance	Cond-to-Cond Nom. Ca	pacitance Cond-to-Other (Cond	ds + Shield) Max. Current	
Element Nor	50				<u> </u>	

Voltage

UL Voltage Rating 300 V (PLTC)

Mechanical Characteristics

Temperature

Bend Radius

Stationary Min. Installation Min.

3.7 in (94 mm)	3.7 in (94 mm)	
Max. Pull Tensio	n:	217 lbs (98.4 kg)
Bulk Cable Weig	ht:	92 lbs/1000ft

Standards and Compliance

Environmental Suitability:	Indoor/Outdoor, Indoor, Sunlight Resistance		
Flammability / Reaction to Fire:	UL 1685 UL Loading, FT4, T-29-520, IEEE 1202, FT4		
NEC / UL Compliance:	Article 725, Article 727, CL3R, ITC-ER, PLTC-ER		
AWM Compliance:	AWM 2464		
European Directive Compliance:	EU CE Mark, EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)		
APAC Compliance:	China RoHS II (GB/T 26572-2011)		

History

Update and Revision:	Revision Number: 0.504 Revision Date: 06-30-2022

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
9312 060500	Chrome	Reel	500 ft	612825227915
9312 0601000	Chrome	Reel	1,000 ft	612825227908

© 2022 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.