

# EEPROM Serial 1-Mb I<sup>2</sup>C - Automotive Grade 1 in Wettable Flank UDFN8 Package

## NV24M01MUW

### Description

The NV24M01MUW is a EEPROM Serial 1-Mb I<sup>2</sup>C – Automotive Grade 1, internally organized as 131,072 words of 8 bits each.

It features a 256-byte page write buffer and supports the Standard (100 kHz), Fast (400 kHz) and Fast-Plus (1 MHz) I<sup>2</sup>C protocol.

Write operations can be inhibited by taking the WP pin High (this protects the entire memory).

External address pins make it possible to address up to four NV24M01MUW devices on the same bus.

On-Chip ECC (Error Correction Code) makes the device suitable for high reliability applications.

### Features

- Automotive AEC-Q100 Grade 1 (–40°C to +125°C) Qualified
- 1.8 V to 5.5 V Supply Voltage Range
- 256-Byte Page Write Buffer
- Hardware Write Protection for Entire Memory
- Schmitt Triggers and Noise Suppression Filters on I<sup>2</sup>C Bus Inputs (SCL and SDA)
- Low Power CMOS Technology
- 1,000,000 Program/Erase Cycles
- 100 Year Data Retention
- Industrial and Extended Temperature Range
- 8-pad UDFN Wettable Flank Package
- These Devices are Pb-Free, Halogen Free/BFR Free and are RoHS Compliant




Figure 1. Functional Symbol




ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)




UDFN-8  
(Wettable Flank)  
MUW3 SUFFIX  
CASE 517DH

### MARKING DIAGRAM



CAW = Specific Device Code  
A = Assembly Location  
WL = Wafer Lot  
Y = Year  
W = Work Week  
▪ = Pb-Free Package

### PIN CONFIGURATION



### PIN FUNCTION

| Pin Name                        | Function       |
|---------------------------------|----------------|
| A <sub>1</sub> , A <sub>2</sub> | Device Address |
| SDA                             | Serial Data    |
| SCL                             | Serial Clock   |
| WP                              | Write Protect  |
| V <sub>CC</sub>                 | Power Supply   |
| V <sub>SS</sub>                 | Ground         |

### ORDERING INFORMATION

See detailed ordering and shipping information on page 9 of this data sheet.

**Table 1. ABSOLUTE MAXIMUM RATINGS**

| Parameters                                         | Ratings      | Units |
|----------------------------------------------------|--------------|-------|
| Storage Temperature                                | –65 to +150  | °C    |
| Voltage on any Pin with Respect to Ground (Note 1) | –0.5 to +6.5 | V     |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The DC input voltage on any pin should not be lower than –0.5 V or higher than  $V_{CC} + 0.5$  V. During transitions, the voltage on any pin may undershoot to no less than –1.5 V or overshoot to no more than  $V_{CC} + 1.5$  V, for periods of less than 20 ns.

**Table 2. RELIABILITY CHARACTERISTICS** (Note 2)

| Symbol                 | Parameter      | Min       | Units                |
|------------------------|----------------|-----------|----------------------|
| $N_{END}$ (Notes 3, 4) | Endurance      | 1,000,000 | Program/Erase Cycles |
| $T_{DR}$               | Data Retention | 100       | Years                |

2. These parameters are tested initially and after a design or process change that affects the parameter according to appropriate AEC–Q100 and JEDEC test methods.
3. Test Condition: Page Mode,  $V_{CC} = 5$  V, 25°C.
4. The device uses ECC (Error Correction Code) logic with 6 ECC bits to correct one bit error in 4 data bytes. Therefore, when a single byte has to be written, 4 bytes (including the ECC bits) are re-programmed. It is recommended to write by multiple of 4 bytes in order to benefit from the maximum number of write cycles.

**Table 3. DC OPERATING CHARACTERISTICS**

$V_{CC} = 1.8$  V to 5.5 V,  $T_A = -40^{\circ}\text{C}$  to  $+125^{\circ}\text{C}$ , unless otherwise specified.

| Symbol    | Parameter          | Test Conditions                                       | Min                                                   | Max            | Units         |
|-----------|--------------------|-------------------------------------------------------|-------------------------------------------------------|----------------|---------------|
| $I_{CCR}$ | Read Current       | Read, $f_{SCL} = 1$ MHz                               |                                                       | 1              | mA            |
| $I_{CCW}$ | Write Current      |                                                       |                                                       | 8.0            | mA            |
| $I_{SB}$  | Standby Current    | All I/O Pins at GND or $V_{CC}$                       | $T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$  | 2              | $\mu\text{A}$ |
|           |                    |                                                       | $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$ | 5              |               |
| $I_L$     | I/O Pin Leakage    | Pin at GND or $V_{CC}$                                | $T_A = -40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$  | 1              | $\mu\text{A}$ |
|           |                    |                                                       | $T_A = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$ | 2              |               |
| $V_{IL1}$ | Input Low Voltage  | $2.5\text{ V} \leq V_{CC} \leq 5.5\text{ V}$          | –0.5                                                  | $0.3 V_{CC}$   | V             |
| $V_{IL2}$ | Input Low Voltage  | $1.8\text{ V} \leq V_{CC} < 2.5\text{ V}$             | –0.5                                                  | $0.2 V_{CC}$   | V             |
| $V_{IH1}$ | Input High Voltage | $2.5\text{ V} \leq V_{CC} \leq 5.5\text{ V}$          | $0.7 V_{CC}$                                          | $V_{CC} + 0.5$ | V             |
| $V_{IH2}$ | Input High Voltage | $1.8\text{ V} \leq V_{CC} < 2.5\text{ V}$             | $0.8 V_{CC}$                                          | $V_{CC} + 0.5$ | V             |
| $V_{OL1}$ | Output Low Voltage | $V_{CC} \geq 2.5\text{ V}$ , $I_{OL} = 3.0\text{ mA}$ |                                                       | 0.4            | V             |
| $V_{OL2}$ | Output Low Voltage | $V_{CC} < 2.5\text{ V}$ , $I_{OL} = 1.0\text{ mA}$    |                                                       | 0.2            | V             |

# NV24M01MUW

**Table 4. PIN IMPEDANCE CHARACTERISTICS**

$V_{CC} = 1.8 \text{ V to } 5.5 \text{ V}$ ,  $T_A = -40^\circ\text{C to } +125^\circ\text{C}$ , unless otherwise specified.

| Symbol                    | Parameter                                                 | Conditions                                   | Max | Units         |
|---------------------------|-----------------------------------------------------------|----------------------------------------------|-----|---------------|
| $C_{IN}$ (Note 5)         | SDA I/O Pin Capacitance                                   | $V_{IN} = 0 \text{ V}$                       | 8   | pF            |
| $C_{IN}$ (Note 5)         | Input Capacitance (other pins)                            | $V_{IN} = 0 \text{ V}$                       | 6   | pF            |
| $I_{WP}$ , $I_A$ (Note 6) | WP Input Current, Address Input Current ( $A_1$ , $A_2$ ) | $V_{IN} < V_{IH}$ , $V_{CC} = 5.5 \text{ V}$ | 75  | $\mu\text{A}$ |
|                           |                                                           | $V_{IN} < V_{IH}$ , $V_{CC} = 3.3 \text{ V}$ | 50  |               |
|                           |                                                           | $V_{IN} < V_{IH}$ , $V_{CC} = 1.8 \text{ V}$ | 25  |               |
|                           |                                                           | $V_{IN} > V_{IH}$                            | 2   |               |

5. These parameters are tested initially and after a design or process change that affects the parameter according to appropriate AEC-Q100 and JEDEC test methods.

6. When not driven, the WP,  $A_1$ ,  $A_2$  pins are pulled down to GND internally. For improved noise immunity, the internal pull-down is relatively strong; therefore the external driver must be able to supply the pull-down current when attempting to drive the input HIGH. To conserve power, as the input level exceeds the trip point of the CMOS input buffer ( $\sim 0.5 \times V_{CC}$ ), the strong pull-down reverts to a weak current source.

**Table 5. AC CHARACTERISTICS** (Note 7)

$V_{CC} = 1.8 \text{ V to } 5.5 \text{ V}$ ,  $T_A = -40^\circ\text{C to } +125^\circ\text{C}$ , unless otherwise specified.

| Symbol                | Parameter                                  | Fast<br>$V_{CC} = 1.8 \text{ V} - 5.5 \text{ V}$ |     | Fast-Plus<br>$V_{CC} = 2.5 \text{ V} - 5.5 \text{ V}$ |       | Units         |
|-----------------------|--------------------------------------------|--------------------------------------------------|-----|-------------------------------------------------------|-------|---------------|
|                       |                                            | Min                                              | Max | Min                                                   | Max   |               |
| $F_{SCL}$             | Clock Frequency                            |                                                  | 400 |                                                       | 1,000 | kHz           |
| $t_{HD:STA}$          | START Condition Hold Time                  | 0.6                                              |     | 0.25                                                  |       | $\mu\text{s}$ |
| $t_{LOW}$             | Low Period of SCL Clock                    | 1.3                                              |     | 0.45                                                  |       | $\mu\text{s}$ |
| $t_{HIGH}$            | High Period of SCL Clock                   | 0.6                                              |     | 0.40                                                  |       | $\mu\text{s}$ |
| $t_{SU:STA}$          | START Condition Setup Time                 | 0.6                                              |     | 0.25                                                  |       | $\mu\text{s}$ |
| $t_{HD:DAT}$          | Data In Hold Time                          | 0                                                |     | 0                                                     |       | $\mu\text{s}$ |
| $t_{SU:DAT}$          | Data In Setup Time                         | 100                                              |     | 50                                                    |       | ns            |
| $t_R$ (Note 8)        | SDA and SCL Rise Time                      |                                                  | 300 |                                                       | 100   | ns            |
| $t_F$ (Note 8)        | SDA and SCL Fall Time                      |                                                  | 300 |                                                       | 100   | ns            |
| $t_{SU:STO}$          | STOP Condition Setup Time                  | 0.6                                              |     | 0.25                                                  |       | $\mu\text{s}$ |
| $t_{BUF}$             | Bus Free Time Between STOP and START       | 1.3                                              |     | 0.5                                                   |       | $\mu\text{s}$ |
| $t_{AA}$              | SCL Low to Data Out Valid                  |                                                  | 0.9 |                                                       | 0.40  | $\mu\text{s}$ |
| $t_{DH}$              | Data Out Hold Time                         | 50                                               |     | 50                                                    |       | ns            |
| $T_i$ (Note 8)        | Noise Pulse Filtered at SCL and SDA Inputs |                                                  | 50  |                                                       | 50    | ns            |
| $t_{SU:WP}$           | WP Setup Time                              | 0                                                |     | 0                                                     |       | $\mu\text{s}$ |
| $t_{HD:WP}$           | WP Hold Time                               | 2.5                                              |     | 1                                                     |       | $\mu\text{s}$ |
| $t_{WR}$              | Write Cycle Time                           |                                                  | 5   |                                                       | 5     | ms            |
| $t_{PU}$ (Notes 8, 9) | Power-up to Ready Mode                     |                                                  | 0.1 |                                                       | 0.1   | ms            |

7. Test conditions according to "A.C. Test Conditions" table.

8. Tested initially and after a design or process change that affects this parameter.

9.  $t_{PU}$  is the delay between the time  $V_{CC}$  is stable and the device is ready to accept commands.

**Table 6. AC TEST CONDITIONS**

|                           |                                                                                                                                                        |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input Levels              | $0.2 \times V_{CC}$ to $0.8 \times V_{CC}$ ( $V_{CC} < 2.5 \text{ V}$ ) and $0.3 \times V_{CC}$ to $0.7 \times V_{CC}$ ( $V_{CC} \geq 2.5 \text{ V}$ ) |
| Input Rise and Fall Times | $\leq 50 \text{ ns}$                                                                                                                                   |
| Output Reference Levels   | $0.5 \times V_{CC}$                                                                                                                                    |
| Output Load               | Current Source: $I_L = 3 \text{ mA}$ ( $V_{CC} \geq 2.5 \text{ V}$ ); $I_L = 1 \text{ mA}$ ( $V_{CC} < 2.5 \text{ V}$ ); $C_L = 100 \text{ pF}$        |

### Power-On Reset (POR)

The NV24M01 incorporates Power-On Reset (POR) circuitry which protects the internal logic against powering up in the wrong state.

The device will power up into Standby mode after  $V_{CC}$  exceeds the POR trigger level and will power down into Reset mode when  $V_{CC}$  drops below the POR trigger level.

*This bi-directional POR behavior protects the device against brown-out failure, following a temporary loss of power.*

### Pin Description

**SCL:** The Serial Clock input pin accepts the Serial Clock signal generated by the Master.

**SDA:** The Serial Data I/O pin receives input data and transmits data stored in EEPROM. In transmit mode, this pin is open drain. Data is acquired on the positive edge, and is delivered on the negative edge of SCL.

**A<sub>1</sub> and A<sub>2</sub>:** The Address pins accept the device address. These pins have on-chip pull-down resistors.

**WP:** The Write Protect input pin inhibits all write operations, when pulled HIGH. This pin has an on-chip pull-down resistor.

### Functional Description

The NV24M01 supports the Inter-Integrated Circuit (I<sup>2</sup>C) Bus data transmission protocol, which defines a device that sends data to the bus as a transmitter and a device receiving data as a receiver. Data flow is controlled by a Master device, which generates the serial clock and all START and STOP conditions. The NV24M01 acts as a Slave device. Master and Slave alternate as either transmitter or receiver. Up to 4 devices may be connected to the bus as determined by the device address inputs A<sub>1</sub> and A<sub>2</sub>.

### I<sup>2</sup>C Bus Protocol

The I<sup>2</sup>C bus consists of two 'wires', SCL and SDA. The two wires are connected to the  $V_{CC}$  supply via pull-up resistors. Master and Slave devices connect to the 2-wire bus via their respective SCL and SDA pins. The transmitting device pulls down the SDA line to 'transmit' a '0' and releases it to 'transmit' a '1'.

Data transfer may be initiated only when the bus is not busy (see A.C. Characteristics).

During data transfer, the SDA line must remain stable while the SCL line is HIGH. An SDA transition while SCL is HIGH will be interpreted as a START or STOP condition (Figure 2).

### START

The START condition precedes all commands. It consists of a HIGH to LOW transition on SDA while SCL is HIGH. The START acts as a 'wake-up' call to all receivers. Absent a START, a Slave will not respond to commands.

### STOP

The STOP condition completes all commands. It consists of a LOW to HIGH transition on SDA while SCL is HIGH. The STOP starts the internal Write cycle (when following a Write command) or sends the Slave into standby mode (when following a Read command).

### Device Addressing

The Master initiates data transfer by creating a START condition on the bus. The Master then broadcasts an 8-bit serial Slave address. The first 4 bits of the Slave address are set to 1010, for normal Read/Write operations (Figure 3). The next 2 bits, A<sub>2</sub>, A<sub>1</sub>, select one of 4 possible memory devices connected on a single I<sup>2</sup>C bus. The A<sub>2</sub> and A<sub>1</sub> bits must match the state of the external address pins. The seventh bit, a<sub>16</sub> is the most significant internal address bit. The last bit, R/ $\overline{W}$ , specifies whether a Read (1) or Write (0) operation is to be performed. To select an internal memory location (data byte) a 17-bit address word is required: a<sub>16</sub> bit from the Slave address byte followed by two address bytes.

### Acknowledge

After processing the Slave address, the Slave responds with an acknowledge (ACK) by pulling down the SDA line during the 9th clock cycle (Figure 4). The Slave will also acknowledge the byte address and every data byte presented in Write mode. In Read mode the Slave shifts out a data byte, and then releases the SDA line during the 9th clock cycle. If the Master acknowledges the data, then the Slave continues transmitting. The Master terminates the session by not acknowledging the last data byte (NoACK) and by sending a STOP to the Slave. Bus timing is illustrated in Figure 5.

# NV24M01MUW




Figure 2. Start/Stop Timing




Figure 3. Slave Address Bits




Figure 4. Acknowledge Timing




Figure 5. Bus Timing

## WRITE OPERATIONS

### Byte Write

In Byte Write mode the Master sends a START, followed by Slave address, two byte address and data to be written (Figure 6). The Slave acknowledges all 4 bytes, and the Master then follows up with a STOP, which in turn starts the internal Write operation (Figure 7). During internal Write, the Slave will not acknowledge any Read or Write request from the Master.

### Page Write

The NV24M01 contains 131,072 bytes of data, arranged in 512 pages of 256 bytes each. The most significant 9 bits of the address word (a16 from the Slave Address byte and most significant Address byte) identify the page and the last 8 bits identify the byte within the page. The 17-bit address word (a16 from the Slave Address byte followed by two address bytes) points to the first byte to be written. Up to 256 bytes can be written in one Write cycle (Figure 8).

The internal byte address counter is automatically incremented after each data byte is loaded. If the Master transmits more than 256 data bytes, then earlier bytes will be overwritten by later bytes in a 'wrap-around' fashion (within the selected page). The internal Write cycle starts immediately following the STOP.

### Acknowledge Polling

Acknowledge polling can be used to determine if the NV24M01 is busy writing or is ready to accept commands. Polling is implemented by interrogating the device with a 'Selective Read' command (see READ OPERATIONS).

The NV24M01 will not acknowledge the Slave address, as long as internal Write is in progress.


### Hardware Write Protection

With the WP pin held HIGH, the entire memory is protected against Write operations. If the WP pin is left floating or is grounded, it has no impact on the operation of the NV24M01. The state of the WP pin is strobed on the last falling edge of SCL immediately preceding the first data byte (Figure 9). If the WP pin is HIGH during the strobe interval, the NV24M01 will not acknowledge the data byte and the Write request will be rejected.


### Delivery State

The NV24M01 is shipped erased, i.e., all bytes are FFh.


**NV24M01MUW**




### Figure 6. Byte Write Timing



### Figure 7. Write Cycle Timing



### Figure 8. Page Write Timing



### Figure 9. WP Timing

## READ OPERATIONS

### Immediate Address Read

In standby mode, the NV24M01 internal address counter points to the data byte immediately following the last byte accessed by a previous operation. If that 'previous' byte was the last byte in memory, then the address counter will point to the 1st memory byte, etc.

When, following a START, the NV24M01 is presented with a Slave address containing a '1' in the R/W bit position (Figure 10), it will acknowledge (ACK) in the 9th clock cycle, and will then transmit data being pointed at by the internal address counter. The Master can stop further transmission by issuing a NoACK, followed by a STOP condition.

### Selective Read

The Read operation can also be started at an address different from the one stored in the internal address counter.

The address counter can be initialized by performing a 'dummy' Write operation (Figure 11). Here the START is followed by the Slave address (with the R/W bit set to '0') and the desired two byte address. Instead of following up with data, the Master then issues a 2nd START, followed by the 'Immediate Address Read' sequence, as described earlier.

### Sequential Read

If the Master acknowledges the 1st data byte transmitted by the NV24M01, then the device will continue transmitting as long as each data byte is acknowledged by the Master (Figure 12). If the end of memory is reached during sequential Read, then the address counter will 'wrap-around' to the beginning of memory, etc. Sequential Read works with either 'Immediate Address Read' or 'Selective Read', the only difference being the starting byte address.




Figure 10. Immediate Address Read Timing




Figure 11. Selective Read Timing




Figure 12. Sequential Read Timing



## NV24M01MUW

### ORDERING INFORMATION

| Device Order Number | Specific Device Marking | Temperature Range | Package Type                       | Shipping <sup>†</sup> |
|---------------------|-------------------------|-------------------|------------------------------------|-----------------------|
| NV24M01MUW3VTBG     | CAW                     | –40°C to +125°C   | UDFN8<br>(Pb-Free, Wettable Flank) | 3000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

10. All packages are RoHS-compliant (Pb-Free, Halogen-free).




SCALE 2:1

### UDFN8 2x3, 0.5P

#### CASE 517DH

#### ISSUE A


DATE 10 DEC 2020




#### NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M,1994.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO PLATED TERMINAL AND IS MEASURED BETWEEN 0.15 AND 0.25MM FROM THE TERMINAL TIP.
4. COPLANARITY APPLIES TO THE EXPOSED PAD AS WELL AS THE TERMINALS.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN.        | NOM. | MAX. |
| A   | 0.45        | 0.50 | 0.55 |
| A1  | 0.00        | ---  | 0.05 |
| A3  | 0.13 REF    |      |      |
| b   | 0.20        | 0.25 | 0.30 |
| D   | 1.90        | 2.00 | 2.10 |
| D2  | 1.30        | 1.40 | 1.50 |
| E   | 2.90        | 3.00 | 3.10 |
| E2  | 1.30        | 1.40 | 1.50 |
| e   | 0.50 BSC    |      |      |
| K   | 0.40 REF    |      |      |
| L   | 0.30        | 0.40 | 0.50 |



#### GENERIC MARKING DIAGRAM\*



XXXXX = Specific Device Code  
 A = Assembly Location  
 WL = Wafer Lot  
 Y = Year  
 W = Work Week  
 ■ = Pb-Free Package

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "■", may or may not be present. Some products may not follow the Generic Marking.

|                  |                 |                                                                                                                                                                                  |
|------------------|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON06579G     | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | UDFN8 2X3, 0.5P | PAGE 1 OF 1                                                                                                                                                                      |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**onsemi Website:** [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

**North American Technical Support:**

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

**Europe, Middle East and Africa Technical Support:**

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative