




Product: [MRG214](#)



MRG2140 - Mil-Spec Coax, 50 Ohm, RG-214, 13 AWG Str SC, Double SC Braid, PVC Jkt, Commercial

Product Description

Mil-Spec Coax, 50 Ohm, RG-214, 13 AWG (7x21) Silvered Copper Conductor, PE Insulation, 95%/90% Silvered Copper Braid Shield, PVC Jacket, Commercial

Technical Specifications

Product Overview

Suitable Applications:	Point-to-point and point-to-multipoint wireless antenna communication; Wireless microphones, Two-Way Radios, Amateur (Ham) Radio, Low Power FM, GPS, RFID (Radio Frequency Identification)
------------------------	--

Construction Details

RG Type:	214
----------	-----

Conductor

No. of Elements	Size	Stranding	Nom. Diameter	Material
1	13 AWG	Stranded	2.25 mm	SCCS - Silvered Copper Covered Steel

Insulation

Material	Nom. Insulation Diameter
PE - Polyethylene	7.25 mm (0.285 in)

Outer Shield

Layer	Outer Shield Type	Material	Coverage
1	Braid	Silvered Copper (SC)	86%
2	Braid	Silvered Copper (SC)	90%

Outer Jacket

Material	Nom. Diameter
PVC - Polyvinyl Chloride	10.8 mm

Table Notes:	According to European Standard EN 50290-2-20
--------------	--

Electrical Characteristics

Return Loss (RL)

Frequency	Min. Return Loss
100 - 1000 MHz	23 dB

Attenuation

Frequency	Nom. Attenuation
50 MHz	4.3 dB/100m
230 MHz	9.9 dB/100m
470 MHz	14.9 dB/100m
860 MHz	21.3 dB/100m
1000 MHz	23.3 dB/100m

Table Notes:	Max. attenuation 10% higher
--------------	-----------------------------

Power Rating

Frequency	Max. Power Rating
-----------	-------------------

100 MHz	760 W
1,000 MHz	175 W

Electricals

Max. Conductor DCR	Nom. Outer Shield DCR	Nom. Capacitance Cond-to-Shield	Nom. Characteristic Impedance	Nom. Velocity of Prop.
6 Ohm/km (1.8 Ohm/1000ft)	3.1 Ohm/km (0.94 Ohm/1000ft)	100 pF/m (30 pF/ft)	50 Ohm	66%

Mechanical Characteristics

Temperature

Operating	Installation	Storage
-40°C To +70°C	-5°C To +50°C	-40°C To +70°C

Bend Radius

Stationary Min.
110 mm (4.3 in)

Bulk Cable Weight:	181 kg/km
--------------------	-----------

Standards and Compliance

Environmental Suitability:	Indoor - Euroclass Eca
Flammability / Reaction to Fire:	IEC 60332-1-2
CPR Compliance:	CPR Euroclass: Eca; CPR UKCA Class: Eca
ISO/IEC Compliance:	IEC 61196
UK Regulation Compliance:	UKCA Mark

History

Update and Revision:	Revision Number: 0.198 Revision Date: 12-22-2023
----------------------	--

Part Numbers

Variants

Item #	Color	Putup Type	Length	EAN
MRG214.0025	Black	Reel	25 m	8719605103123
MRG214.00100	Black	Reel	100 m	8719605103116
MRG214.00200	Black	Reel	200 m	8719605181602
MRG214.00500	Black	Reel	500 m	8719605103130

© 2024 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.