

LNX-1204G-10G-SFP

12-Port Industrial Gigabit Unmanaged Ethernet Switch, with 8*10/100/1000Tx, 2*1G SFP Slots, and 2*10G SFP+ Slots



Features


- ▶ Supports 8*10/100/1000Tx, 2*1G SFP Slots, and 2*10G SFP+ Slots
- ▶ Store-and-Forward Switching Architecture
- ▶ 60Gbps Back-Plane (Switching Fabric)
- ▶ 16K MAC Address Table
- ▶ 9.6Kbytes Jumbo Frame Support
- ▶ Redundant Power Input Design: 12~48VDC
- ▶ Built-in 1 Relay Output for Power Failure Warning
- ▶ IP30 Rugged Metal Case Design
- ▶ DIN-Rail and Wall Mount Support Included
- ▶ Operating Temperature Range: -40°C~65°C
- ▶ 5-Year Warranty

INTRODUCTIONS

Antaira Technologies' LNX-1204G-10G-SFP are industrial gigabit unmanaged Ethernet switches featuring 8*10/100/1000Tx Gigabit Ethernet ports, 2*1G SFP slots, and 2*10G SFP+ slots which provide options for long-distance fiber connections, making it ideal for applications that demand high bandwidth and long-distance communication.

The LNX-1204G-10G-SFP are IP30 rated and DIN-rail mountable. These Ethernet switches are designed to support an operating temperature range from -40° to 65°C and are perfect industrial networking products to support any applications that require high bandwidth or high-density connections, such as power/utility, water wastewater treatment, oil/gas/mining, process control automation, security access control systems, and intelligent transportation systems.

DIMENSIONS



Unit: mm (inch)

Din-rail

Wall-mount

SPECIFICATIONS

Technology	
Standards	IEEE 802.3 10Tx Ethernet
	IEEE 802.3u 100Tx Fast Ethernet
	IEEE 802.3ab 1000Tx Gigabit Ethernet
	IEEE 802.3z 1000X Gigabit Fiber
	IEEE 802.3ae 10 Gigabit Ethernet
Processing Type	Store and Forward
Protocol	CSMA/CD
Flow Control	IEEE 802.3x back pressure flow control
Switch Properties	
Switch Architecture	Back-Plane (Switching Fabric): 60.0Gbps 14,880pps for 10Base-T Ethernet 148,800pps for 100Base-T Fast Ethernet 1,488,000pps for 1000Base-T Gigabit Ethernet
Transfer Rate	14,880,000pps for 10 Gigabit Ethernet Port
Packet Buffer	8Mbits
Jumbo Frame	9.6Kbytes
MAC Table Size	16K
Port Interface	
Ethernet Port	8*10/100/1000Tx Auto negotiation speed, Full/Half duplex mode, and auto MDI/MDI-X connection
SFP Port	2*1G SFP slots 2*10G SFP+ slots
LED Indicators	System: Power 1, Power 2, Fault Ethernet Ports: On-Link/Flash-data transmitting SFP: On-Link/Flash-data transmitting
Network Cable	10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m) 1000BaseTX: 4-pair UTP/STP Cat.5/5E cable EIA/TIA-568 100-ohm (100m)

Mechanical Characteristics	
Housing	Metal, IP30 protection
Dimension	54 x 142 x 99 mm
Weight	Unit: 2.35 lbs.; Shipping: 2.97 lbs.
Mounting	DIN-Rail mounting, Wall mounting
Power Requirement	
Input Voltage	12~48VDC Redundant Input
Power Connection	1 removable 6-contact terminal block
Relay Contact	24VDC, 1A resistive
Overload Current Protection	Present
Power Reverse Polarity Protection	Present
System Power Consumption	11.3W
Environmental Limits	
Operating Temperature	-40°C to 65°C
Storage Temperature	-40°C ~ 85°C
Ambient Relative Humidity	5 to 95%, (non-condensing)
Regulatory Approvals	
EMI	FCC Part 15 Subpart B Class A, CE EN55032/EN61000-6-4 Class A
EMS	CE EN55035/EN61000-6-2 Class A, IEC61000-4-2,3,4,5,6,8
Free Fall	IEC60068-2-32
Shock	IEC60068-2-27
Vibration	IEC60068-2-6
Green	RoHS Compliant
Certifications	FCC, CE, UL 61010-1, 61010-2-201
Warranty	5 Years

ORDERING INFO

LNX-1204G-10G-SFP	12-Port Industrial Gigabit Unmanaged Ethernet Switch, with 8*10/100/1000Tx, 2*1G SFP Slots, and 2*10G SFP+ Slots
--------------------------	--