


IZ5046



Inductive sensor

IZB31,5-BPKG/AS-514-TPS



Product characteristics

Electrical design	PNP
Output function	normally open
Sensing range [mm]	1.5
Housing	cylindrical
Dimensions [mm]	Ø 4 / L = 41

Electrical data

Operating voltage [V]	10...30 DC
Current consumption [mA]	10; (24 V)
Reverse polarity protection	yes

Outputs

Electrical design	PNP
Output function	normally open
Max. voltage drop switching output DC [V]	3
Permanent current rating of switching output DC [mA]	100
Switching frequency DC [Hz]	1800
Short-circuit protection	yes
Type of short-circuit protection	pulsed
Overload protection	yes

Detection zone

Sensing range [mm]	1.5
Real sensing range S_r [mm]	$1.5 \pm 10\%$
Operating distance [mm]	0...1.2

Accuracy / deviations

Correction factor	steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3
Hysteresis [% of S_r]	< 15
Switch point drift [% of S_r]	-10...10

Operating conditions

Ambient temperature [°C]	-25...80
Protection	IP 67



Inductive sensor

IZB31,5-BPKG/AS-514-TPS

Tests / approvals		
EMC	EN 60947-5-2	
	EN 55011	class B
MTTF [years]		835
UL approval	Ta	0...40 °C
	power supply	Class 2
	File number UL	E174191

Mechanical data		
Weight [g]		19
Housing		cylindrical
Mounting		non-flush mountable
Dimensions [mm]		Ø 4 / L = 41
Materials		housing: stainless steel; sensing face: POM

Displays / operating elements		
Display	switching status	4 x 90° LED, red

Accessories		
Items supplied		Mounting clamps: 1


Remarks		
Pack quantity		1 pcs.

Electrical connection - plug

Connector: 1 x M8; coding: A



Connection



IZ5046




Inductive sensor

IZB31,5-BPKG/AS-514-TPS

Diagrams and graphs

Installation



If S_r varies by $< 10\%$ the following free space must be maintained ferromagnetic materials $X > 1.5\text{ mm}$ other metals $X > 3.0\text{ mm}$