

1		2		3		4																																									
						<table border="1"><thead><tr><th>Part No.</th><th>Cable color</th></tr></thead><tbody><tr><td>~088Y1T~</td><td>GRAY</td></tr><tr><td>~088Y2T~</td><td>BLACK</td></tr><tr><td>~088Y3T~</td><td>WHITE</td></tr></tbody></table>		Part No.	Cable color	~088Y1T~	GRAY	~088Y2T~	BLACK	~088Y3T~	WHITE																																
Part No.	Cable color																																														
~088Y1T~	GRAY																																														
~088Y2T~	BLACK																																														
~088Y3T~	WHITE																																														
NOTE 1 We indicate the length of the harness on the last of product name, 'L' part. 2 The angle is optional for long length in the case of L>250. 3 Tolerance for [L]		<table border="1"><thead><tr><th>Length L [mm]</th><th>Tolerance [mm]</th></tr></thead><tbody><tr><td>100 ≤ L ≤ 200</td><td>± 4 mm</td></tr><tr><td>200 < L ≤ 500</td><td>± 8 mm</td></tr><tr><td>500 < L ≤ 1000</td><td>±12 mm</td></tr></tbody></table>		Length L [mm]	Tolerance [mm]	100 ≤ L ≤ 200	± 4 mm	200 < L ≤ 500	± 8 mm	500 < L ≤ 1000	±12 mm	【 DIMENSIONS OF CONNECTOR 】																																			
Length L [mm]	Tolerance [mm]																																														
100 ≤ L ≤ 200	± 4 mm																																														
200 < L ≤ 500	± 8 mm																																														
500 < L ≤ 1000	±12 mm																																														
⚠ For L longer than 1000mm or shorter than 100mm, please contact our representatives. 4. Specifications are subject to change without notice.																																															
【 PRECAUTIONS FOR HANDLING 】 1. Connector insertion and extraction (1) Insert the connector as perpendicularly to the mating surface as possible with aligning the mating axes of both connectors by specialised insertion JIG. Part No.: U.FL(A)-LP-IN.OUT (CL331-2401-0) (fig.1) ◆ Do not excessively slant the connectors when inserting. (2) Connector shall be extracted by specialised extraction JIG. Part No.: U.FL(A)-LP-IN.OUT (CL331-2401-0) (fig.2) ◆ Never hold the cable when extracting the cable because it damages the connector. 2. Allowable loads on the cable after the connectors are mated. The below figures show the maximum allowable loads on the cable. (fig.3) ◆ Do not apply loads exceeding these values to the cable.																																															
<table border="1"><thead><tr><th>No.</th><th>Part No.</th><th>Code No.</th><th>No.</th><th>Part No.</th></tr></thead><tbody><tr><td>1</td><td>U.FL(A)-LP(P)-088</td><td>CL331-2400-0</td><td>2</td><td>1.37 Dia. coaxial cable</td></tr></tbody></table>		No.	Part No.	Code No.	No.	Part No.	1	U.FL(A)-LP(P)-088	CL331-2400-0	2	1.37 Dia. coaxial cable	<table border="1"><thead><tr><th>No.</th><th>Part No.</th><th>Code No.</th><th>No.</th><th>Part No.</th></tr></thead><tbody><tr><td>1</td><td>U.FL(A)-LP(P)-088</td><td>CL331-2400-0</td><td>2</td><td>1.37 Dia. coaxial cable</td></tr></tbody></table>		No.	Part No.	Code No.	No.	Part No.	1	U.FL(A)-LP(P)-088	CL331-2400-0	2	1.37 Dia. coaxial cable	<table border="1"><thead><tr><th>No.</th><th>Part No.</th><th>Code No.</th><th>No.</th><th>Part No.</th></tr></thead><tbody><tr><td>1</td><td>U.FL(A)-LP(P)-088</td><td>CL331-2400-0</td><td>2</td><td>1.37 Dia. coaxial cable</td></tr></tbody></table>		No.	Part No.	Code No.	No.	Part No.	1	U.FL(A)-LP(P)-088	CL331-2400-0	2	1.37 Dia. coaxial cable	<table border="1"><thead><tr><th>No.</th><th>Part No.</th><th>Code No.</th><th>No.</th><th>Part No.</th></tr></thead><tbody><tr><td>1</td><td>U.FL(A)-LP(P)-088</td><td>CL331-2400-0</td><td>2</td><td>1.37 Dia. coaxial cable</td></tr></tbody></table>		No.	Part No.	Code No.	No.	Part No.	1	U.FL(A)-LP(P)-088	CL331-2400-0	2	1.37 Dia. coaxial cable
No.	Part No.	Code No.	No.	Part No.																																											
1	U.FL(A)-LP(P)-088	CL331-2400-0	2	1.37 Dia. coaxial cable																																											
No.	Part No.	Code No.	No.	Part No.																																											
1	U.FL(A)-LP(P)-088	CL331-2400-0	2	1.37 Dia. coaxial cable																																											
No.	Part No.	Code No.	No.	Part No.																																											
1	U.FL(A)-LP(P)-088	CL331-2400-0	2	1.37 Dia. coaxial cable																																											
No.	Part No.	Code No.	No.	Part No.																																											
1	U.FL(A)-LP(P)-088	CL331-2400-0	2	1.37 Dia. coaxial cable																																											
UNITS mm		SCALE FREE		COUNT 2		DESCRIPTION OF REVISIONS DIS-D-00006986		DESIGNED MS. MATSUMOTO		CHECKED MT. KANEKO		DATE 20210323																																			
APPROVED NK. NINOMIYA 20200220		CHECKED MT. KANEKO 20200220		DESIGNED MK. INOUE 20200220		DRAWN MK. INOUE 20200220		DRAWING NO. UFL-2LPA-088Y*T-A-L		PART NO. 1		CODE NO. 1																																			