ATO FUSE BLOCKS WITH COMMON HOT FEEDS







Accepts standard two-blade ATO fuses or simple style

Recessed area in the middle of the block accepts a label

Standard 1/4" snap-on quick connect automotive

circuit breakers 6V - 32V DC. Contacts are recessed for safety.

for ready identification of circuits.

style terminals.

Specifications Overview

Max Fuse Rating:	30A maximum per circuit, 150A total
Input Terminal Rating:	100A maximum (#10-32 stud)
Torque Rating:	2.25Nm max.
Ground Feed:	#10-32 stud and .250" blades
Termination:	.250" x .032" quick connect terminals; input wire size: #4-6 AWG; Output wire size: #12-16 AWG
Mounting:	four #10 screws @ 0.9Nm
Temperature Rating:	-18 °C (0 °F) to 65 °C (150 °F)

Web Resources

Download technical resources at: **littelfuse.com/AFB**

Ordering Information

COMMON HOT FEED ONLY:		
PART NUMBER	POSITIONS	DIMENSIONS
46377-6	6	2.47" (62.73mm) x 3.375" (85.72mm) x 0.812" (20.62mm)
46377-8	8	3.09" (78.48mm) x 3.375" (85.72mm) x 0.812" (20.62mm)
46377-10	10	3.72" (94.48mm) x 3.375" (85.72mm) x 0.812" (20.62mm)
46377-12	12	4.34" (110.23mm) x 3.375" (85.72mm) x 0.812" (20.62mm)
46377-18	18	6.22" (157.98mm x 3.375" (85.72mm) x 0.812" (20.62mm))

COMMON HOT FEED & COMMON GROUND:

PART NUMBER	POSITIONS	DIMENSIONS
46379-6	6	3.77" (95.75mm) x 3.375" (85.72mm) x 0.812" (20.62mm)
46379-8	8	4.39" (111.50mm) x 3.375" (85.72mm) x 0.812" (20.62mm)
46379-10	10	5.02" (127.50mm) x 3.375" (85.72mm) x 0.812" (20.62mm)

Visit Littelfuse.com for the most up-to-date product information. Littelfuse products are designed for specific applications and should not be used for any purpose (including, without limitation, automotive applications) not expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse product documentation and should not be used for any purpose not expressly set forth in applicable Littelfuse product documentation. Littelfuse for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse product documentation.

Datasheet Replaces Hotfeed Number D-601

•

•

٠