



The diagram illustrates the assembly of the Amphenol connector. Component 1 is the connector head, which includes a locking mechanism and a central pin. Component 2 is a shield sleeve that fits over the head. Component 3 is a dielectric sleeve that fits over the shield sleeve. Component 4 is the outer jacket, which is the final protective layer. The components are shown in an exploded view, indicating their relative positions and how they fit together.

UNLESS OTHERWISE SPECIFIED TOLERANCE TO BE		THIS DOCUMENT IS THE PROPERTY OF AMPHENOL AUSTRALIA PTY. LTD. NO PART THEREOF MAY BE REPRODUCED AND USED WITHOUT THE PRIOR WRITTEN CONSENT OF THE OWNER		1	FIRST ISSUE	MH	24-01-12	---
LINEAR	ANGULAR	CAD FILE:	051: MH	REV.	CHANGE DETAILS	BY	DATE	CHG/N
$X \times X \pm 0.1$ 0.05	$X^\circ \pm 30'$ 0.05	TITLE:		Amphenol Amphenol Australia Pty Ltd, 7 Riverside Street, Kyburghwood, VIC3103				
BREAK ALL SHARP EDGES AND REMOVE ALL BURRS		MAT'L: REFER TO COMPONENT	CKD: M.N.H	DATE: 24-01-12	SHORT MALE RCA PLUG CUSTOMER DWG			
DO NOT SCALE	FINISH: REFER TO TABLE	APP'D: PM	DATE: 24-01-12	DRAWINGS NO.				
DIMENSIONS IN MILLIMETRES	THREE ANGLE CHECKS	SIZE: 2:1 UMS	PART NO:	REFER TO TABLE	SIZE: A3	5510808-000-1		
						SHEET		