https://www.golter.com/product/duplicate-golter-mobile-charger-for-ev-2-in-1-type2-35kw-230v-lrd-portable-wallbov-5m-1



## Qoltec Mobile charger for EV 2-in-1 Type2 with regulation | 3.5kW | 230V | LCD | Portable | Wallbox | 5m

Product code: 52465

Mobile charger by Qoltec with Type 2 connector, which is the standard on the European market and fits any Type 2 cable for charging an electric car, and SCHUKO plug powered from a 230V outlet. The charger with adjustable charging current will provide you with convenient and safe charging of your electric car battery.

- Type 2 connector
- LCD display
- Adjustable charging current
- Delayed start function
- Easy wall mounting
- 5m cable.

### THE BEST SOLUTION FOR CHARGING ELECTRIC VEHICLES



### Fast charging, Universal connection, Ideal for long trips

Don't let the low charge of your battery prevent you from using your electric vehicle. With the Qoltec mobile charger you can charge your car battery in just a few hours. The portable charger is perfect for longer holiday trips, for example, thanks to its compact design, it takes up little space and can easily be transported directly in the boot or in the included bag. The charger can be plugged in anywhere with access to a 230V earthed power socket and you can enjoy your independence as you cover the distance.

WWW.QOLTEC.COM 1/8


### **EUROPEAN STANDARD CONNECTOR TYPE 2**



# High charging power, 7-pin type 2 connector compliant with current regulations, Four options (8A, 10A, 13A, 16A) for optimal charging The charger has a Type 2 connector, which is now an official European Union standard, and will charge electric cars equipped with a suitable charging socket. The Type 2 connector is

The charger has a Type 2 connector, which is now an official European Union standard, and will charge electric cars equipped with a suitable charging socket. The Type 2 connector is contacts, of which 3 contacts or 5 are for charging and 2 for communication between the station and the car supports four current modes of 8A, 10A, 13A and 16A. It is worth mentioning that the Type 2 connector is designed for electric vehicles with a charging power of more than 3kW.

WWW.QOLTEC.COM 2/8



# Convenient 2.4" LCD display, Monitoring of accurate charging time, Temperature sensor for safe charger operation, Automatic error repair.

The product is equipped with a multifunctional, 2.4" LCD display and LEDs indicating charging status. On the display we can:

- set the current value using the a button : 8A, 10A, 13A, 16A;
- check the exact charging time,
- set the charging time delay simply by using the button with the clock icon,
- monitor the operating temperature of the charger in real time thanks to the built-in plug temperature sensor, the charger will immediately interrupt operation if the safe value is exceeded and will automatically resume operation when the temperature returns to a normal level,
- monitor the progress of the charging process,

#### Automatic error repair

In addition, the charger has an intelligent chip that automatically corrects errors during charging, reacting accordingly if any of the parameters exceed the norm, ensuring stable charger operation.

### **DELAYED CHARGING FUNCTION**



### Intuitive operation, Intelligent charging delay function for 1, 2, 5 or 8 hours

You can set a delayed charging start time of 1, 2, 5 or even 8 hours and save on energy costs by, for example, using the night-time tariff, this is more economical as we are not overcharging the system. Simply connect the charger to the power supply and then press the delay button a certain number of times before connecting the car. By pressing the button with the clock icon, charging is delayed by 1 hour after each click.

WWW.QOLTEC.COM 3/8

#### CHARGE AT HOME OR ON THE ROAD



# Enjoy a 5m charging cable with ergonomic plug for convenience and ease of use. If you want to mount the EV charger on a wall you should choose a suitable location for this, preferably close to the car and the power source. You will also need to install a residual current

If you want to mount the EV charger on a wall you should choose a suitable location for this, preferably close to the car and the power source. You will also need to install a residual current circuit breaker - a type B RCD is the best choice as a means of full complementary protection. Ensure that it is in a location that is protected from moisture, free from any mechanical damage and not exposed to direct sunlight. Be absolutely sure that this is the case. A high level of convenience will be provided by the 5 m charging cable with ergonomic plug.

### **AESTHETIC AND PRACTICAL WALL MOUNTING**



### Practical wall bracket for mounting the loader gun

The charging gun can be conveniently mounted on the wall for easy access and space saving, especially in confined spaces. The wall mount stabilizes the cable and gun, protecting them from accidental damage and from dirt. With the wall mount, the user can organize the charging station, which enhances the aesthetics and functionality of the charging area in both home garages and commercial parking lots.

WWW.QOLTEC.COM 4 / 8

### WATER-RESISTANT POLYCARBONATE HOUSING



Durable and Atmospheric Resistant housing made of non-flammable polycarbonate, Easy external mounting, Water and dust resistant

Our chargers are constructed from durable, UV-resistant, non-flammable polycarbonate. In addition, the charger exhibits high water resistance and is dustproof. The casing has special holes

for external mounting.

5/8 WWW.QOLTEC.COM

### BE ECOLOGICAL AND POWER YOUR CAR WITH CLEAN ENERGY



# Use your own solar energy to charge your car, Recharge your vehicle up to several times faster

Use your own renewable clean energy from photovoltaics to charge your car – a way to reduce your car's running costs and your carbon footprint. You can recharge your car at any time and even several times faster. The number of panels you will need to charge your car will depend on the characteristics of your battery, the model of your vehicle and the distances you travel. You can charge it in two ways:

- while the **photovoltaic panels are producing energy** this is the most cost-effective solution
- using the excess energy produced by the photovoltaic panels, which is returned to energy storage or the grid and can be used at a later date.

WWW.QOLTEC.COM 6 / 8

#### THE SAFETY OF YOU AND YOUR LOVED ONES IS IMPORTANT TO US



### Advanced safety features that protect both the car and the user.

When designing the chargers, we put safety first. You can now charge your car safely and quickly. The product has advanced safety features and has LEDs that change colour depending on the current status.

### **CONFIDENCE CONFIRMED BY A WARRANTY**

### Product comes with a 24-month warranty

Do you care about the high quality of the product you are buying? Our solutions will meet your expectations. The chargers we offer come with a purchase.

24-month guarantee from the date of

**TECHNICAL DATA** 

WWW.QOLTEC.COM 7/8

Producer	Qoltec
Туре	2
Number of phases	1
Maximum power	3.5kW
Rated voltage	230V
Operating current	16/13/10/8A
Frequency	50Hz
Plug type	Schuko 16A
Insulation resistance	>10M
Type of charging interface	IEC 62196-2
Cross-section conductor of a cable	3*2.5mm +1*0.5m
Diameter of the cable	10.8mm
Cable length	5m
Insulation material	TPU
Display	LCD 2,4*
Compatibility	TYPE 2 compatible with most electric cars in Europe
Safety	Over voltage protection Over current protection Ungrounded protection Temperature monitoring Short circuit protection Leakage protection
IP Rating	IP65
Working temperature	-30°C ~ +50°C
Notices	Only use the charger if the mains supply is fitted with a residual current circuit breaker Do not attempt to repair the appliance yourself Please do not use the device with an additional power supply
OTHER PARAMETERS	
Colour	Black, green
Dimensions (D/L x W x H)	215 x 95 x 60 mm (charger)  235 x 70 x 62 mm (plug )   120 x 385 x 345 (bag)
Package contents	1 x EV charger 1 x Wall mounting bracket for charger 1 x Mounting screws 1 x Charger storage bag 1 x User manual 1 x Warranty card
Package	Box
Package depth / length [mm]	340
Package width [mm]	410
Package height [mm]	140
Net weight [kg]	2.800
Gross weight [kg]	3.400
Certificate	CE
Warranty	24 month
EAN code	5901878524658

WWW.QOLTEC.COM 8/8