






RoHS Compliant



Section P-P



N = Number of poles
Dim A = $N \times 11.0 + 2.0$
Dim B = $(N - 1) \times 11.0$

Pol.	Tol.	Dim A & B
2-4p		± 0.20
5-11p		± 0.30
17-18p		± 0.40

REV	SIGN	DATE	DESCRIPTION	APPROVER
B	△	10/14'09	Terminal screw plated is changed from Ni plated to Zinc plated	Aaron
C	△	05/28'11	Add the P.C.B LAYOUT	Tason
	△	05/28'11	Critical dimension is changed.	Tason
	△	05/28'11	The tolerance table is changed.	Tason
D	△	01/04'12	The design is changed.	Chen Bo
	△	01/04'12	The Dimension 6.5 are added	Chen Bo
E	△	12/11'12	Update the drawing	Jacky
F	△	2021.02.26	Add the TUV approval	Devin
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				

MATERIALS:

- 1) BODY: THERMOPLASTICS, UL94-V0 BLACK
2) TERMINAL: BRASS, 0.8t, Tin PLATED
3) TERMINAL SCREWS WITH WASHER: STEEL, Zinc PLATED, M4.0 △
4) COVER: PC, TRANSPARENT

ELECTRICAL:	cULus	EN/IEC 60947-7-4 △
Rated Voltage & Current:	300 V, 30 A	500V, 32A △
Withstand Voltage:	AC 2000 V/Min	
Rated Impulse Withstand Voltage:		6.0KV △
Insulation Resistance:	1000 MΩ OR MORE AT DC 500 V	
Wave Soldering Temperature:	260°C±5°C/5 Sec	
Operating Temperature range:	-40 °C ~ +115 °C	
Screw Torque Values:	15 Kgf.cm	1.2-1.8N.m △
Wire Range:	22 - 10AWG	0.34-4mm ² △

- △ Critical dimension:
Approval:

YK 701xx 2 x x 00G
G RoHS compliant (lead<4%) In copper Alloy

NO. OF POLES
02: 2 POLES
03: 3 POLES
04: 4 POLES
:
18: 18 POLES

MARK
0: "@" MARK
1: "ANY" MARK

TERMINAL & SCREW PLATED

- 0: TERMINAL & SCREW: G/F
△ 1: TERMINAL: G/F, SCREW: Zinc
2: TERMINAL: Sn, SCREW: G/F
△ 3: TERMINAL: Sn, SCREW: Zinc

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YK701 With cover and W/o flange SERIES			
PART NO.	YK701xx2xx00G	DWG NO.	8YK0001-701		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		Devin 2021.02.26	Devin 2021.02.26		X. ± 0.50 X.X ± 0.30 X.XX ± 0.10 X° $\pm 1^\circ$
				SHEET: 01/01	UNIT: mm SCALE: NONE REV.: F