

Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Commercial product name: ELASTOSIL® E41
TRANSPARENT

This substance/ mixture contains nanoforms (according to REACH Regulation)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:

Industrial.

adhesives.

1.3 Details of the supplier of the safety data sheet

Manufacturer/distributor: Wacker Chemie AG
Street/POB-No.: Gisela-Stein-Straße 1
State/postal code/city: D 81671 München
Telephone: +49 89 6279-0

Contact point: Wacker Chemicals Ltd.

Street/POB-No.: 2 Arlington Square, Downshire Way

Postal code/city: Bracknell RG12 1WA
Country: United Kingdom
Telephone: +44 1344 401 670

Information about the Safety Data Sheet: Telephone +49 8677 83-4888

eMail WLCP-MSDS@wacker.com

1.4 Emergency telephone number

Emergency Information: +44 1273 289451

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567):

Classification	H-Code
Long-term (chronic) aquatic hazard, Category 3	H412
Flammable liquids, Category 2	H225
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2	H319
Reproductive toxicity, Category 2	H361d
Specific target organ toxicity - repeated exposure, Category 2	H373

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567):

Pictogram(s):







Signal Word: Danger

H-Code	Hazard Statements
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H361d	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

H412	Harmful to aquatic life with long lasting effects.
P-Code	Precautionary Statements
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P243	Take action to prevent static discharges.
P260	Do not breathe vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to
P338	do. Continue rinsing.
P313	Get medical advice/ attention.
P405	Store locked up.

Hazard ingredients (labelling):

Toluene

2.3 Other hazards

No data available.

Endocrine disrupting properties - human health: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties - environment: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Polydimethylsiloxane + auxiliary + silane + solvent



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

3.2.2 Hazardous ingredients

silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica			>=10 - <25 %	
CAS-No.: 68909-20-6	EC-No.: 272-697-1	Index-No.: 014-052-00-7		
INHA [1]				
Classification (REGULATION (EC	C) No STOT RE 2, by	inhalation / H373 (Lungs)		
1272/2008 as amended by GB-C	LP EUH066			
Regulation, UK SI 2019/720, and	UK SI			
2020/1567) *				
Curathatic amorphaus cilican diavida, panastrusturad material, cilonizad				

Synthetic amorphous silicon dioxide, nanostructured material, silanized

Particle Size Distribution:

Type of distribution: number distribution, State during measurement: agglomerates, d50 = 100 - 750 μm, Measurement technique: laser diffraction<u>Particle Size Distribution:</u>

Type of distribution: number distribution, State during measurement: aggregates, d50 = 60 - 300 nm, Measurement technique: Transmission Electron Microscopy / Electron Microscopy (TEM/EM) calculationType of distribution: number distribution, State during measurement: Primary structure, d50 = 6 - 50 nm, Measurement technique: Transmission Electron Microscopy / Electron Microscopy (TEM/EM) calculation

Form / Aspect Ratio (:1):

Form: fractal aggregates, Aspect Ratio (:1): 1 - 3, Measurement technique: TEM

Crystallinity:

Crystallinity: amorphous, Measurement technique: X-ray Diffraction (XRD)

Chemical Surface Functionalisation:

Chemical Surface Functionalisation: none, Properties of Coated Particle: hydrophobic

Specific surface: 40 - 350 m²/g

Toluene			>10 - <20 %
CAS-No.: 108-88-3 EC-	C-No.: 203-625-9	Index-No.: 601-021-00-3	
INHA [1], [2] REA	ACH No.: 01-211947131	0-51	
Classification (REGULATION (EC) No	o Aquatic Chronic 3 /	H412; Repr. 2 / H361d; STOT RE 2 / H373; STC	OT SE 3 / H336;
1272/2008 as amended by GB-CLP	Skin Irrit. 2 / H315; /	Asp. Tox. 1 / H304; Flam. Liq. 2 / H225	
Regulation, UK SI 2019/720, and UK S	SI		
2020/1567) *			

Triacetoxymethylsilane		>5 – <10 %
CAS-No.: 4253-34-3	EC-No.: 224-221-9	
INHA [1]	REACH No.: 01-2119962266-32	
Classification (REGULATION (EC)) No Skin Corr. 1C / H314; Acute Tox. 4, oral / H302; Eye Dam. 1 / H318	3
1272/2008 as amended by GB-CL	.P EUH014	
Regulation, UK SI 2019/720, and I	JK SI	
2020/1567) *		

Di-n-butyltin diacetate		>=0,025 - <0,1 %
CAS-No.: 1067-33-0 EC-No	o.: 213-928-8	
INHA [1] REAC	CH No.: 01-2119634587-29	
Classification (REGULATION (EC) No 1272/2008 as amended by GB-CLP	Skin Corr. 1B / H314; Muta. 2 / H341; Repr. 1B / H360D; Repr. 1B /	·
Regulation, UK SI 2019/720, and UK SI	1 / H372 (Immune system); Aquatic Acute 1 / H400; Aquatic Chronic Dam. 1 / H318; Skin Sens. 1B / H317; STOT SE 1 / H370 (thymus)	517 H410, Eye
2020/1567) *	M-Factor, Acute = 10	
	M-Factor, Chronic = 10	

Type: INHA: ingredient, VERU: impurity

REACH registered substances may be included as impurities. These do not necessarily require identified uses and exposure scenarios in the safety data sheet.

[1] = Hazardous or environmentally harmful substance; [2] = substance with a Community workplace exposure limit; [3] = PBT substance; [4] = vPvB substance; [5] = Endocrine disrupting properties

^{*}Classification codes are explained in section 16.



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

The hazards associated with respirable particulate exposure do not apply to this material. All fillers, pigments and similar ingredients are incorporated in a non-respirable form, and under normal conditions of use are expected to remain inextricably bound within the product.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above ≥ 0.1%.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or if you feel unwell seek medical advice (show label or SDS where possible). Vapours may cause dizziness. Do not leave affected individuals unattended. Pregnant women exposed to this substance must seek medical advice.

After contact with the eyes:

Rinse immediately with plenty of water. Seek medical advice in case of continuous irritation.

After contact with the skin:

Wash with plenty of water or water and soap. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

After inhalation:

Provide fresh air.

After swallowing:

Give several small portions of water to drink. Do not induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

After exposure, specialist advice (e.g. gynaecology/birth aid or, if necessary, toxicology/human genetics) is recommended. Product contains reproductive toxins (may cause harm to the unborn child and /or impairs male or female reproductive function).

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

water mist, extinguishing powder, alcohol-resistant foam, carbon dioxide, sand.

Extinguishing media which must not be used for safety reasons:

water jet .

5.2 Special hazards arising from the substance or mixture

Risk of hazardous gasses or fumes in the event of fire. Exposure to combustion products may be a health hazard! Hazardous combustion products: carbon oxides , silicon oxides , incompletely burnt hydrocarbons , toxic and very toxic fumes . Heavy soot formation during combustion.

5.3 Advice for firefighters

Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air. Use tightly fitting chemical protection suit (see section 8). Keep unprotected persons away.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Secure the area. Wear personal protection equipment (see section 8). Task force: Use tightly fitting chemical protection suit (see section 8). Keep unprotected persons away. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Do not walk through spilled material. Ensure adequate ventilation. If material is released indicate risk of slipping.



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

6.2 Environmental precautions

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

6.3 Methods and material for containment and cleaning up

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with liquid, mainly acid binding material and dispose of according to local/state/federal regulation. For large amounts: Liquids may be recovered using suction devices or pumps. If flammable, only air driven or properly rated electrical equipment should be used. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

Further information:

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Observe notes under section 7.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Precautions for safe handling:

Ensure adequate ventilation. Must be syphoned off in situ. Spilled substance increases risk of slipping. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Observe information in section 8. Keep away from incompatible substances in accordance with section 10.

Precautions against fire and explosion:

Product may release acetic acid. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:

Observe local/state/federal regulations.

Advice for storage of incompatible materials:

Observe local/state/federal regulations.

Further information for storage:

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

Minimum temperature allowed during storage and transportation: 0 °C

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum airborne concentrations at the workplace:

maximum an borne concorning	nono at tino montpiaco.				
Substance	Туре	mg/m³	ppm	Dust fract.	Fibre/m ³
Toluene	OEL	191,0	50,0		
Toluene	EU	192,0	50,0		
Acetic acid	OEL	25,0	10,0		
Acetic acid	EU	25,0	10,0		

Toluene: STEL (EU) is 384 mg/m3 (=100 ppm), can be absorbed through the skin.

Acetic acid: The short-time value of the EU threshold isime value of the EU threshold is 50 mg/m3 (= 20 ppm).



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

Derived No-Effect Level (DNEL):

I	Ol	u	er	1	е	
۸		_	_	r		

Area of use:	Value:
Worker; by inhalation; systemic (acute) local (acute)	384 mg/m³
Worker; by inhalation; systemic (long term) local (long term)	192 mg/m³
Worker; dermal; systemic (long term)	384 mg/kg bw/day
Consumer; by inhalation; systemic (acute) local (acute)	226 mg/m ³
Consumer; by inhalation; systemic (long term)	56,5 mg/m³
Consumer; dermal; systemic (long term)	226 mg/kg bw/day
Consumer; oral; systemic (long term)	8,13 mg/kg bw/day

Triacetoxymethylsilane

Area of use:	Value:
Worker; by inhalation; systemic (long term) systemic (acute)	25 mg/m ³
Worker; dermal; systemic (long term) systemic (acute)	14,5 mg/kg/day
Consumer; by inhalation; local (long term) local (acute)	5,1 mg/m³
Consumer; dermal; systemic (long term) systemic (acute)	7,2 mg/kg/day
Consumer; oral; systemic (long term) systemic (acute)	1 mg/kg/day

Predicted No Effect Concentration (PNEC):

Toluene

Area of use:	Value:	
freshwater	0,68 mg/l	
marine water	0,68 mg/l	
Intermittent release	0,68 mg/l	
Sediment	16,39 mg/kg dry mass	
Sediment (marine water)	16,39 mg/kg dry mass	
Soil	2,89 mg/kg dry mass	
sewage treatment plant	13,61 mg/l	

Triacetoxymethylsilane

Area of use:	Value:
freshwater	1,0 mg/l
	The value was derived for the corresponding silanetriol
	(hydrolysis product).
marine water	0,10 mg/l
	The value was derived for the corresponding silanetriol
	(hydrolysis product).
Intermittent release	10 mg/l
	The value was derived for the corresponding silanetriol
	(hydrolysis product).
Sediment (freshwater)	0,80 mg/kg wet weight
	The value was derived for the corresponding silanetriol
	(hydrolysis product).
Sediment (marine water)	0,080 mg/kg wet weight
	The value was derived for the corresponding silanetriol
	(hydrolysis product).
Soil	0,13 mg/kg wet weight
	The value was derived for the corresponding silanetriol
	(hydrolysis product).
sewage treatment plant	10 mg/l



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:

Avoid exposure - obtain special instructions before use. Avoid exposure of the substance to pregnant women. Observe standard industrial hygiene practices for the handling of chemical substances. Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Do not eat, drink or smoke when handling. Preventive skin protection recommended. Wash hands at the end of work and before eating. Keep working clothes separately. Remove contaminated, soaked clothing immediately. Clean work areas regularly. Use with adequate ventilation. Provide emergency shower and eye-bath. Keep away from foodstuff, drink and feedingstuff.

Further information for system design and engineering measures

Observe information in section 7. Observe national regulatory requirements.

Personal protection equipment:

Respiratory protection

If inhalative exposure above the occupational exposure limit cannot be excluded, adequate respiratory protection equipment must be used. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136. Recommended Filter type: Gas filter type ABEK (certain inorganic, organic and acidic gases and vapors; ammonia/amines), according to acknowledged standards such as EN 14387

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Suitable respiratory equipment: Respirator with a full face mask, according to acknowledged standards such as EN 136.

Recommended Filter type: Combined filter type ABEK-P2 (certain inorganic, organic and acidic gases and vapors; ammonia/amines; particles), according to acknowledged standards such as EN 14387

For long or intense exposure, use respiratory protective equipment. Suitable respiratory equipment: Positive pressure self contained breathing apparatus, according to acknowledged standards such as EN 137.

Observe the equipment manufacturer's information and wear time limits for respirators.

Eye protection

tight fitting protective goggles, according to acknowledged standards such as EN 166.

Hand protection

Protective gloves are required at all times when handling the material, according to recognized standards such as EN374.

Recommended glove types: Protective gloves made of fluorinated rubber

thickness of the material: > 0,7 mm Breakthrough time: > 480 min

Recommended glove types: Protective gloves made of 5-layer laminate of PE and EVOH (4H)

thickness of the material: 0,062 mm Breakthrough time: > 480 min

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. Note that, due to the numerous external influences (such as temperature), a chemically resistant protective glove in daily use may have a service life that is considerably shorter than the measured break through time.

Skin protection

Chemical protective clothing, according to acknowledged standards such as EN 13034, full-body liquid-tight protection if necessary, according to acknowledged standards such as EN 14605, if handled uncovered. Please observe the instructions regarding permeability time which are provided by the supplier. antistatic protective clothing, according to acknowledged standards such as EN 1149 and antistatic working shoes, according to acknowledged standards such as ISO 20345 and ISO 20347.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters, drains or sewers and soil.



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Property:	Value:	Method:
Physical state:	liquid	
Colour:	colourless	
Odour:	strong	
Odour Threshold:	no data available	
Melting point:	exempt	
Boiling point/boiling range:	111 °C at 1013 hPa	(not specified)
Lower explosion limit:	1,2 Vol-%	(not specified)
Upper explosion limit:	7 Vol-%	(not specified)
Flash point:	6 °C	(DIN 53213)
Ignition temperature:	540 °C	(DIN 51794)
Thermal decomposition:	exempt	
pH:	Not applicable. Insoluble in water.	
Viscosity, kinematic:	not applicable	
Viscosity, dynamic:	65000 mPa.s at 23 °C	(Brookfield)
Water solubility:	practically insoluble	
Partition coefficient: n-octanol/water:	not applicable	
Vapour pressure:	29 hPa at 20 °C	(not determined)
Density:	1,078 g/cm³ (23 °C)	(DIN 53217)
Relative vapour density:	no data available	
Particle Size Distribution:	Not applicable.	

9.2 Other information

Solubility in water: Hydrolytic decomposition occurs. pH Value: Product displays acidic reaction with water.

Explosion limits for released acetic acid: 4 - 17%(V).

Property: Value: Method:

SECTION 10: Stability and reactivity

10.1 - 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known. Violent reactions are possible with various chemicals.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

Moisture, heat, open flames, and other sources of ignition.

10.5 Incompatible materials

Reacts violently with: water, basic substances and alcohols. The reaction takes place with the formation of acetic acid.

10.6 Hazardous decomposition products

Acetic acid by hydrolysis.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

11.1.1 General information

Data derived for the product as a whole are of higher priority than data for single ingredients.



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

11.1.2 Acute toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Acute toxicity estimate (ATE): ATE_{mix} (Oral): > 2000 mg/kg

Data on substances:

Toluene:

Exposure routes	Result/Effect
Oral	LD50 5580 mg/kg
	Species: Rat, Source: ECHA
dermal	LD50 12267 mg/kg
	Species: Rabbit, Source: ECHA
by inhalation	LC50 28,1 mg/l; 4 h
(vapour)	Species: Rat, Source: ECHA

11.1.3 Skin corrosion/irritation

Product details:

irritating

The given result is based on an evaluation of the whole database for this endpoint ("weight of evidence").

(Species: Rabbit, Source: Conclusion by analogy)

Data on substances:

Toluene:

irritating

(Species: Rabbit, Method: OECD 404, Source: ECHA)

11.1.4 Serious eye damage/eye irritation

Product details:

irritatina

The given result is based on an evaluation of the whole database for this endpoint ("weight of evidence").

(Species: Rabbit, Source: Conclusion by analogy)

Data on substances:

Toluene:

No eye irritation

(Species: Rabbit, Method: OECD 405, Source: ECHA)

11.1.5 Respiratory or skin sensitisation

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Toluene:

Exposure routes	Result	
Skin contact	Does not cause skin sensitisation.	
	(Species: Guinea pig, Test system: Maximisation Test, Method: OECD 406, Source: ECHA)	

11.1.6 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

Data on substances:

Toluene:

negative

(Metabolic activation: with and without metabolic activation, Test system: mutation assay (in vitro) / mouse lymphoma cells,

Method: OECD 476, Source: ECHA)

negative

(Metabolic activation: with and without metabolic activation, Test system: mutation assay (in vitro) / bacterial cells, Method: OECD 471, Source: ECHA)

negative

(Test system: chromosome aberration assay (in vivo), Species: Rat, Application Route: Intraperitoneal, Cell type: bone marrow cells, Source: ECHA)

11.1.7 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances

Toluene:

The substance can possibly impair the unborn child in humans.

11.1.9 Specific target organ toxicity - single exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Toluene:

Result/Effect

Exposure routes: by inhalation

target organs: Central nervous system

Vapours may be narcotising.

Source: ECHA

11.1.10 Specific target organ toxicity - repeated exposure

Assessment:

For this endpoint no toxicological test data is available for the whole product.

Data on substances:

Toluene:

Target organs in animal experiments: Central nervous system.

11.1.11 Aspiration hazard

Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

Data on substances:

Toluene:

Product can pose an aspiration hazard.

11.2 Information on other hazards



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

11.2.1 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Data on substances:

Toluene:

No data available.

11.2.2 Further toxicological information

In contact with dampness product separates a small quantity of acetic acid (64-19-7) which irritates skin and mucous membranes.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

For the product as a whole, no test data is available. D4 is an unavoidable contamination in the manufacture of silicone polymers and leads to adverse effects on aquatic organisms under laboratory conditions. The release of D4 from a polysiloxane matrix is limited thermodynamically by the partition equilibrium silicone/water. Thus, only that portion of the D4 content that gets into the aqueous phase contributes to the environmental hazard of the overall product. For the classification according to the summation method this is being considered applying correction factors.

Data on substances:

Data derived for the product as a whole are of higher priority than data for single ingredients.

Toluene:

Result/Effect	Species/Test system	Source
LC50: 5,5 mg/l (measured)	flow-through test	ECHA
	Oncorhynchus kisutch (coho salmon) (96 h)	
EC50: 3,78 mg/l (measured)	semi-static test	ECHA
	Daphnia (water flea) (48 h)	
EC50 (photosynthesis): 134 mg/l (nominal)	algae (3 h)	ECHA
NOEC (Growth): 1,39 mg/l	Oncorhynchus kisutch (coho salmon) (40 d)	ECHA
NOEC (reproduction rate): 0,74 mg/l	Ceriodaphnia dubia (water flea) (7 d)	ECHA

12.2 Persistence and degradability

Assessment:

Polymer component: biologically not degradable. Elimination by adsorption to activated sludge.

Data on substances:

Toluene:

Readily biodegradable.

12.3 Bioaccumulative potential

Assessment:

Polymer component: No adverse effects expected.

12.4 Mobility in soil

Assessment:

Polymer component: insoluble in water.

12.5 Results of PBT and vPvB assessment

No data available.

Data on substances:



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

Toluene:

No data available.

12.6 Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Data on substances:

Toluene:

No data available.

12.7 Other adverse effects

none known

Additional information

In cross-linked state not soluble in water. Easily separable from water by filtration.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

Recommendation:

Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

13.1.3 Waste Disposal Legislation Ref.No.(EC)

It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

n-Propanol)

n-Propanol)

SECTION 14: Transport information

ADR: 3

14.1	UN number or ID number	
	ADR	UN1993 UN1993
14.2	Proper shipping name	
	ADR (Domestic transport regulations): RID	Entzündbarer flüssiger Stoff, n.a.g. (enthält Toluen und n-Pr Flammable liquid, n.o.s (contains toluene and n-propanol) Entzündbarer flüssiger Stoff, n.a.g. (enthält Toluen und n-Pr Flammable liquid, n.o.s (contains toluene and n-propanol) Flammable liquid, n.o.s. (contains toluene and n-propanol) Flammable liquid, n.o.s. (contains toluene and n-propanol)
14.3	Transport hazard class	

(Limited quantity (LQ): 1L)



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

RID:	3
IMDG:	3
ICAO/IATA	

14.4 Packing group

ADR :: II
RID :: II
IMDG :: II
ICAO/IATA :: II

14.5 Environmental hazards

Environmentally hazardous: no Marine pollutant (IMDG): no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Maritime transport in bulk according to IMO instruments

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

Control of Major Accident Hazards Regulations 2015 (COMAH)

Listed in Directive	Ser. number in list	Qualifying Quantity 1	Qualifying Quantity 2
FLAMMABLE LIQUIDS	P5c	5 000 t	50 000 t

Relevant regulations:

SI 2002/1689: CHIP Regulations 2002 SI 2002/2677: COSHH Regulations 2002

SI 1999/3242: Management of Health & Safety at Work Regulations 1999

Health & Safety at Work Act 1974

SI 1993/1643: Environmental Protection Act 1993 & Subsidiary Regulations.

Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.

Other specifications, restrictions and prohibitions:

REACh Annex XVII: This product contains toluene in an amount of over 0.1 wt.%. Annex XVII, entry 48, of regulation 1907/2006, in its current version, must be taken into account.

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals: Banned and/or restricted

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors - ANNEX I. RESTRICTED EXPLOSIVES PRECURSORS: Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors - ANNEX II. REPORTABLE EXPLOSIVES PRECURSORS: Not applicable

Details of international registration status

Relevant information about individual substance inventories, where available, is given below.



Material: 60003726 **ELASTOSIL® E41 TRANSPARENT**

Print Date 17.04.2025 Version 7.1 (GB) Date of last alteration: 06.02.2025

This product is listed in, or complies with, the substance inventory. (For a correct

interpretation of the New Zealand status, additional information like GHS

classification or Group Standard is required.)

This product is listed in, or complies with, the substance inventory.

This product is listed in, or complies with, the substance inventory.

Canada DSL (Domestic Substance List):

This product is listed in, or complies with, the substance inventory.

This product is listed in, or complies with, the substance inventory.

United States of America (USA)...... TSCA (Toxic Substance Control Act Chemical Substance Inventory):

All components of this product are listed as active or are in compliance with the substance inventory.

This product is listed in, or complies with, the substance inventory. General note:

The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of

this obligation.

European Economic Area (EEA)...... : REACH (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA

by customers or other downstream users must be fulfilled by the latter.

South Korea (Republic of Korea): AREC (Act on Registration and Evaluation of Chemicals; "K-REACH"):

Please approach your regular contact for more detailed information.

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Material 16.1

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on www.wacker.com. WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Key or legend to abbreviations and acronyms used in the safety data sheet

ABEK - Multi-Range Filter A. B. E. K: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: APF - Assigned Protection Factor: CAS No. - Chemical Abstracts Service Registry Number: DFG - German Research Foundation: DIN

- German institute for standardization; DOC - Dissolved Organic Carbon; d/w - days per week; EC / CE / EG - European

Community; EC50 / CE50 - Median effective concentration; ECHA - European Chemicals Agency; ED - endocrine disruptor; EG-



Material: 60003726 ELASTOSIL® E41
TRANSPARENT

Version 7.1 (GB) Print Date 17.04.2025 Date of last alteration: 06.02.2025

RL - test method according to Regulation 440/2008; EN - European Standard; ERC - Environmental Release Category; g/cm3 gram per cubic centimeter; h - hour(s); H-Code - hazard statement code(s); hPa - Hectopascal; IATA Regs - International Air Transport Association (IATA) Dangerous Goods Regulations: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 / Cl50 - half maximal inhibitory concentration; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IMDG Code - International Maritime Dangerous Goods Code: ISO - International Organization for Standardization; LC50 / CL50 - medium lethal concentration; LD50 / DL50 medium lethal dose; LOAEC - Lowest Observed Adverse Effect Concentration; LOAEL - Lowest Observed Adverse Effect Level; MARPOL - International Convention for the Prevention of Marine Pollution from Ships; mg/g - milligrams per gram; mg/kg milligrams per kilogram; mg/l - milligrams per liter; mg/m³ - milligrams per cubic meter; min - minutes; mJ - millijoule; mm millimeter; mm²/s - square millimeter per second; mPa.s - Millipascal second(s); MSDS / SDB / SDS - safety data sheet; No Observed Adverse Effect Concentration: NOAEL - No Observed adverse effect level: NOEC - No Observed Effect Concentration: NOEL - No Observed Effect Level: OECD - Organization for Economic Cooperation and Development: PBT - persistent. bioaccumulative, toxic; PC - product category; P-Code - precautionary statement code(s); ppm - parts per million; PROC process category; RCP - reciprocal calculation-based procedure; RID - convention concerning international carriage by rail; SU sector of use; SVHC - substance of very high concern; Vol% - volume percent; UN No. - United Nations Dangerous Goods Number; vPvB - very Persistent, very Bioaccumulative

Explanation of the GHS classification code:

STOT RE 2; H373:	Specific target organ toxicity - repeated exposure Category 2; May cause damage to organs through
SIOI RE 2 H3/3	Specific fatuet organ toxicity - teneated expositie Category 2. May cause damage to organs intolign
0101112,11070	opositio target organ textotty repeated exposure eategory 2, may eaded damage to organic tribugh

prolonged or repeated exposure if inhaled.

EUH066 Repeated exposure may cause skin dryness or cracking.

Aquatic Chronic 3; H412 : Long-term (chronic) aquatic hazard Category 3; Harmful to aquatic life with long lasting effects.

Repr. 2; H361d............ Reproductive toxicity Category 2; Suspected of damaging the unborn child.

STOT RE 2; H373: Specific target organ toxicity - repeated exposure Category 2; May cause damage to organs through

prolonged or repeated exposure.

STOT SE 3; H336: Specific target organ toxicity - single exposure Category 3; May cause drowsiness or dizziness.

Skin Irrit. 2; H315: Skin corrosion/irritation Category 2; Causes skin irritation.

Asp. Tox. 1; H304: Aspiration hazard Category 1; May be fatal if swallowed and enters airways.

Flam. Liq. 2; H225.....: Flammable liquids Category 2; Highly flammable liquid and vapour.

Skin Corr. 1C; H314...: Skin corrosion/irritation Category 1C; Causes severe skin burns and eye damage.

Acute Tox. 4; H302: Acute toxicity Category 4; Harmful if swallowed.

Eye Dam. 1; H318.....: Serious eye damage/eye irritation Category 1; Causes serious eye damage.

EUH014 Reacts violently with water.

Skin Corr. 1B; H314 ...: Skin corrosion/irritation Category 1B; Causes severe skin burns and eye damage.

Muta. 2; H341...... Germ cell mutagenicity Category 2; Suspected of causing genetic defects.

Repr. 1B; H360D....... Reproductive toxicity Category 1B; May damage the unborn child.

Repr. 1B; H360F Reproductive toxicity Category 1B; May damage fertility.

STOT RE 1; H372: Specific target organ toxicity - repeated exposure Category 1; Causes damage to organs through

prolonged or repeated exposure.

Aquatic Acute 1; H400: Short-term (acute) aquatic hazard Category 1; Very toxic to aquatic life.

Aquatic Chronic 1; H410 : Long-term (chronic) aquatic hazard Category 1; Very toxic to aquatic life with long lasting effects.

Eye Dam. 1; H318.....: Serious eye damage/eye irritation Category 1; Causes serious eye damage.

Skin Sens. 1B; H317..: Skin sensitisation Category 1B; May cause an allergic skin reaction.

STOT SE 1; H370: Specific target organ toxicity - single exposure Category 1; Causes damage to organs.

Classification	Rationale:
Long-term (chronic) aquatic hazard, Category 3	Calculation method
Flammable liquids, Category 2	On basis of test data.
Skin corrosion/irritation, Category 2	On basis of test data.
Serious eye damage/eye irritation, Category 2	On basis of test data.
Reproductive toxicity, Category 2	Calculation method
Specific target organ toxicity - repeated exposure, Category 2	Calculation method

- End of Safety Data Sheet -