

SKINDICHT® MR-M

SKINDICHT® MR-M, reducer, enables the use of cable gland with smaller connection threads than the existing threaded holes



Connector with standard housing unit



Reliability



Space requirement

Benefits

Enables the use of cable glands with smaller connection threads than the existing threaded holes

Application range

Machines
Devices
Housings

Product Make-up

Metric connection thread acc. to DIN EN 60423
Basis for technical information DIN IEC 62444

Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

On request:

Also available with pre-installed O-ring

Material:

Nickel-plated brass

Temperature range:

-60°C to +200°C

Last Update (06.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

SKINDICHT® MR-M**Note**

Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.

**SKINDICHT® MR-M**

Article number	Thread, male M1	Thread, female M2
SKINDICHT® MR-M		
52104310	16 x 1.5	12 x 1.5
52104311	20 x 1.5	12 x 1.5
52104312	20 x 1.5	16 x 1.5
52104313	25 x 1.5	16 x 1.5
52104314	25 x 1.5	20 x 1.5
52104315	32 x 1.5	20 x 1.5
52104316	32 x 1.5	25 x 1.5
52104317	40 x 1.5	25 x 1.5
52104318	40 x 1.5	32 x 1.5
52104319	50 x 1.5	32 x 1.5
52104320	50 x 1.5	40 x 1.5
52104321	63 x 1.5	40 x 1.5
52104322	63 x 1.5	50 x 1.5
52006575	72 x 2	63 x 1.5
SKINDICHT® MR-M, blank brass		
52006579	80 x 2	75 x 1.5

Last Update (06.04.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16