Bell suction cup (round)

FSG 7 HT1-60 M5-AG

Part no.:10.01.06.01237

https://www.schmalz.com/10.01.06.01237



Homepage > Vacuum Technology for Automation > Vacuum Components > Vacuum Suction Cups > Bellows Suction Cups (Round) > Bellows Suction Cups FSG (2.5 Folds) > FSG 7 HT1-60 M5-AG


Bellows suction cup (round) for very uneven workpieces



Size: 7
Suction cup material:
High temp material HT1
Material hardness: 60 °Sh
Material property: imprint-free
Nipple material: Aluminium
Vacuum connection: M5-M

Number of folds: 2.5

Design Data



Attribute	Value
d2	1.8 mm
dn	2.5 mm
Dmax(S)	9 mm
Ds	5.9 mm
G1	M5-AG
Н	19 mm
LG1	5 mm
SW1	7 mm
Z (Stroke)	3 mm

Technical Data

Bell suction cup (round)

FSG 7 HT1-60 M5-AG

Part no.:10.01.06.01237

https://www.schmalz.com/10.01.06.01237



Attribute	Value
Suction cup material	High temp material HT1
Material hardness [Shore A]	60 Shore A
Size	7
Number of folds	2.5
Connection	M5-AG
Curve radius (min) (convex)	7.5 mm
Volume	0.043 cm ³
Suction force (-600mbar)	0.15 N
Pull-off force	0.9 N
Hose diameter (empf.) d	2 mm
Weight	1.6 g
Product family	FSG

Note: Suction force: The specified suction forces are theoretical values at a vacuum of -0.6 bar and with a smooth, dry workpiece surface - they do not include a safety factor Pull-off force: The pull-off force of the versions made of natural rubber is reduced by about 40% Hose diameter: The recommended hose diameter refers to a hose length of approx. 2 m

Spare Parts



SA-NIP N016 M5-AG DN250

Part no.10.01.06.00123
Suction cup connection nipple

Nipple: N 016
Thread G1: M5-M
Overall length: 16 mm
Fitting length: 5 mm
Nominal size: 2,50 mm
Material: Aluminium

Bell suction cup (round)

FSG 7 HT1-60 M5-AG

Part no.:10.01.06.01237

https://www.schmalz.com/10.01.06.01237





FG 7 HT1-60 N016

Part no.10.01.06.01251

Bellows suction cup (round) for very uneven workpieces

Size: 7

Suction cup material: High temp material HT1 Material hardness: 60 °Sh Number of folds: 2.5

Material property: imprint-free