

EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable



1627599

<https://www.phoenixcontact.com/pl/produkty/1627599>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



CHARX connect comfort, AC charging cable, with vehicle charging connector and open cable end, For charging electric vehicles (EV) with alternating current (AC) via GB/T vehicle charging inlets, with protective cap, GB/T, GB/T 20234.2-2015, GB/T 18487.1-2015, housing: black, gray, PHOENIX CONTACT logo, cable: 5 m, black, straight

Product Description

AC charging cable with vehicle charging connector and free cable end for charging electric vehicles (EV) with alternating current (AC) via GB/T vehicle charging inlets, for installation at charging stations for e-mobility (EVSE)

Your advantages

- Complete product range
- Convenient handling due to the ergonomic, triple award-winning design
- Available with your logo on request – for consistent branding of your charging station
- Longitudinal water tightness reliably prevents water ingress
- Developed and produced in accordance with the IATF 16949 automotive standard and ISO 9001
- Tested in accordance with automotive standards LV124, LV214, and LV215-2
- Tested in accordance with EV Ready 37 requirements

Commercial Data

Item number	1627599
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	XWBAAF
Product Key	XWBAAF
Catalog Page	Page 27 (C-7-2019)
GTIN	4055626342801
Weight per Piece (including packing)	1,420 g
Weight per Piece (excluding packing)	1,320 g
Customs tariff number	85444290
Country of origin	PL

EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable



1627599

<https://www.phoenixcontact.com/pl/produkty/1627599>

Technical Data

Product properties

Product type	AC charging cable
Product family	CHARX connect comfort
Application	For charging electric vehicles (EV) with alternating current (AC) via GB/T vehicle charging inlets for installation at charging stations for electromobility (EVSE)
Type	AC charging cable with vehicle charging connector and open cable end
Design	with protective cap
Locking type	No locking option for U-lock
Affixed logo	PHOENIX CONTACT logo
Charging mode	Mode 3, Case C
Charging standard	GB/T

Electrical properties

Type of signal transmission	Pulse width modulation
Note on the connection method	Crimp connection, cannot be disconnected
Coding	680 Ω (between PE and CC)
Type of charging current	AC single-phase
Charging power	4 kW
Charging current	16 A

Power contact

Number	3 (L, N, PE)
Rated voltage	250 V
Rated current	16 A

Signal contact

Number	2 (CP, CC)
Rated voltage	30 V AC
Rated current	2 A

Dimensions

Vehicle charging connector

Width	58 mm
Height	151.3 mm
Depth	238.7 mm

Vehicle charging connector

Width	58 mm
Height	151.3 mm
Depth	238.7 mm

EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable



1627599

<https://www.phoenixcontact.com/pl/produkty/1627599>

Material specifications

Color (Housing)	black (9005)
	black (9005)
	black (9005)
	black (9005)
	black (9005)
Material (Vehicle charging connector)	Plastic
	TPE-U
	Silver

Cable/line

Cable length	5 m
Wiring standards/regulations	prEN 50620 / DIN EN 50620
Wiring certifications	VDE
Cable weight	max. 163 kg/km
Cable type	Class 5
Cable type	straight
Cable structure	3 x 2.5 mm ² + 1 x 0.5 mm ²
External cable diameter	10.2 mm ±0.3 mm
Outer sheath, material	TPE-U
Stripping length of the sheath	70 mm ±5 mm
Cable resistance	≤ 0.00798 Ω/m (based on a power core, at an ambient temperature of 20°C)
Bending radius	min. 153 mm (15x diameter)
Cable type	Class 5
Wiring certifications	VDE
Wiring standards/regulations	prEN 50620 / DIN EN 50620

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 10000
Insertion force	< 100 N
Withdrawal force	< 100 N

Environmental and real-life conditions

Ambient conditions

Degree of protection Vehicle charging connector	IP55 (plugged in; when plugged in and ready to operate, the degree of protection is only ensued if both plug-in components are original products from Phoenix Contact or suitable standard-compliant products)
	IP54
Ambient temperature (operation)	-30 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	5000 m (above sea level)

EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable



1627599

<https://www.phoenixcontact.com/pl/produkty/1627599>

Standards and regulations

Standards

Standards/regulations	GB/T 20234.2-2015
	GB/T 18487.1-2015


EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable

1627599

<https://www.phoenixcontact.com/pl/produkty/1627599>

Drawings

Schematic diagram




Operating instructions

EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable

1627599


<https://www.phoenixcontact.com/pl/produkty/1627599>

Schematic diagram



Pin assignment of the Vehicle Connector

Schematic diagram



Terminology definition


EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable



1627599

<https://www.phoenixcontact.com/pl/produkty/1627599>

Dimensional drawing



Make sure that the vehicle charging connector is placed in an appropriate charging connector holder, which ensures a minimum protection rating of IP24 in accordance with IEC 61851-1, for the entire time between charging. To create this charging connector holder, use the dimensions of the vehicle charging connector. Detailed dimensions can also be found in the Download area.

EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable



1627599

<https://www.phoenixcontact.com/pl/produkty/1627599>

Classifications

ECLASS

ECLASS-9.0	27144705
ECLASS-10.0.1	27144705
ECLASS-11.0	27144705

ETIM

ETIM 8.0	EC002897
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

1627599
<https://www.phoenixcontact.com/pl/produkty/1627599>

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 10;
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

EV-GBG3C-1AC16A-5,0M2,5ESBK01 - AC charging cable



1627599

<https://www.phoenixcontact.com/pl/produkty/1627599>

Accessories

EV-GBAC-PARK - Charging connector holder

1624142

<https://www.phoenixcontact.com/pl/produkty/1624142>



CHARX connect, Charging connector holder, Accessories, for vehicle charging connectors on charging stations (EVSE), GB/T, GB/T 20234.2, Front mounting, housing: black

G-INS-M20-S68N-PNES-BK - Cable gland

1411133

<https://www.phoenixcontact.com/pl/produkty/1411133>



Cable gland, material for screw connection: PA, external cable diameter 6 mm ... 12 mm, shielding: no, connecting thread: M20 x 1.5, color: jet black RAL 9005

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT Sp. z o.o.
ul. Bierutowska 57-59, Budynek nr 3/A
51-317 Wrocław
71/ 39 80 410
pxcpl@phoenixcontact.pl